Propane Checklist for Fair Vendors

Propane Container Filled On Site:

Must be 10' from a source of ignition (open flame, motor)

Propane Container Not Filled On Site Must be 5' from a source of ignition

All Propane Containers

- 1. Must be installed upon a firm, level surface and on a paved surface or solid concrete blocks. 20# cylinders may be set in a milk crate.
- 2. Must be provided with a means of stabilizing the cylinder to prevent falling over.
- 3. Must be protected from vehicle damage at all times.
- 4. Spare propane cylinders must be secured at all times.
- 5. Propane cylinders must be kept qualified. This qualification runs out 12 years after manufacture. Cylinders must be re-qualified after this date expires or taken out of service.

Regulators

- 1. Regulator vents must be 3' from any source of ignition.
- 2. Regulators must be supported and protected from damage at all times.

Appliances

- 1. All appliances, owned or rented, must have a listed gas shut off valve within 6' of the appliance. The tank shut off does not qualify.
- 2. Unlisted outdoor cooking appliances must maintain clearances to combustibles and must not be located under combustible construction. 36" sides and back. 48" front.
- 3. Appliances must be placed on a firm, level foundation. Not earth.
- 4. Propane lines or hoses must be supported and protected from damage at all times.
- 5. Propane hoses must be properly marked LP-GAS, 350 PSI Working Pressure or Propane.
- 6. A qualified fire extinguisher must be present at all times.

Propane & Natural Gas Board 35 State House Station, Augusta, ME 04333-0035

Phone: 207-624-8608